



GLACIER FL22

EXTENDED LIFE COOLANT / ANTIFREEZE

PRODUCT DESCRIPTION:

GLACIER FL22 is a ready-to-use, prediluted ethylene glycol-based coolant that incorporates a time-tested formula without amines and silicates. Designed as an extended-life radiator antifreeze, it provides reliable protection and long-lasting performance for modern engine cooling systems.

APPLICATION:

GLACIER FL22 is a prediluted coolant with frost and rust protection for year-round use in automotive engines.

FEATURES & BENEFITS:

- Outstanding corrosion protection
- Contains no amines, nitrites or phosphates
- Universal application at passenger cars and commercial vehicles.
- Anti-cavitation, preventing foam and the retention of air, ensuring the good performance of the pump.
- Prevents the build-up of deposits, keeping the cooling system clean.
- Long life service product

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

| | | |
|---|-----------------------------------|-------------------------|
| GM 08CLAG01050 Honda E Coolant | Mazda 000077508E20 | Nissan KE90299944 |
| Ford VC-10-A2 | Mazda C100CL005A4X | Subaru Coolant 16218 |
| Hyundai 00232-19010 | Mazda C122CL005A4X | Suzuki Longlife Coolant |
| Hyundai 07100-00200 | Mazda FL22 Coolant | WSS-M97B55 |
| Hyundai 07100-00400 • Hyundai Long Life Coolant | Nissan Anti-freeze Coolant (L250) | |
| | Nissan KE90299934 | |

TYPICAL PROPERTIES:

| PARAMETERS | ASTM | UNIT | GLACIER FL22 |
|------------------|-------|-------|--------------|
| pH | D1278 | cSt | 8 |
| Freezing Point | D1177 | °C | -40 |
| Boiling Point | D1120 | cSt | 110 |
| Density at 15.5C | D4052 | g/cm3 | TBR |

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internol reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internol.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.