

**GLACIER TYPE D**
READY TO USE COOLANT**PRODUCT DESCRIPTION:**

GLACIER Type D is a new-generation, ready-to-use, ethylene glycol-based antifreeze/coolant. It is entirely free from silicates, nitrites, amines, phosphates, and boron, ensuring optimal performance and compatibility with modern cooling systems.

APPLICATION:

It is recommended for use in the internal combustion engines of cars, trucks, construction machinery, agricultural tractors and stationary engines.

FEATURES & BENEFITS:

- Outstanding corrosion protection
- Contains no amines, nitrites or phosphates
- Excellent antifoaming properties.
- Anti-cavitation, preventing retention of air, ensuring the good performance of the pump.
- Prevents the build-up of deposits, keeping the cooling system clean.
- Long life service product

PERFORMANCE LEVELS / MEETS OR EXCEEDS:

Renault/ RVI Type D	ASTM D 3306
AFNOR NF R 15-601	SAE J 1034
BS 6580/5117	

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	GLACIER TYPE D
pH	D1278	cSt	8.3
Freezing Point	D1177	°C	-26
Boiling Point	D1120	cSt	111
Density at 15.5°C	D4052	g/cm3	TBR

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internol reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internol.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.