



MOXIETECH L 220-EP

PRODUCT DESCRIPTION:

MOXIETECH L 220-EP is a versatile, extreme-pressure grease formulated with a lithium 12-hydroxystearate soap thickener and high-quality mineral base oil. Enriched with extreme pressure and proven performance-enhancing additives, this grease is engineered for a wide variety of applications. It is particularly suited for use in steel mills, heavy-duty plain and rolling element bearings operating under severe conditions, including shock loading and wet environments. Additionally, it is ideal for gearbox applications requiring semi-fluid grease and centralized chassis lubrication systems.

APPLICATIONS

MOXIETECH L 220-EP grease is specifically recommended for steel mill, heavy-duty plain and rolling element bearings operating under severe conditions including shock loading and wet environments, gear box application where semi fluid grease is required and for centralized chassis lubrication systems.

PRODUCT ADVANTAGES

- The operating temperature range is -20°C to 130°C
- Excellent anti-wear and extreme pressure properties
- Excellent mechanical stability
- Good resistance to water-washout
- Excellent oxidation stability

TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE		
NLGI Grade	-	00	0	1
Thickener Type	-	Lithium Soap	Lithium Soap	Lithium Soap
Appearance	Visual	Smooth & Homogenous		
Color	Visual	Yellow to Light Brown		
Base Oil	-	Mineral	Mineral	Mineral
Work Penetration @25°C	ASTM D217	400-430	355-385	310-340
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b	1b	1b
Dropping Point °C, Min	ASTM D2265	N/A	190	190
Four Ball Weld Load Kgf, Min	IP239	250	250	250
Four Ball Wear Scar Dia, mm, Max	ASTM D2266	0.6	0.6	0.6
Operating Temperature Range, °C	INTERNAL	-20 to 130		
Base Oil Viscosity @40°C (Cst)	ASTM D445	220	220	220

DISCLAIMER: The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internol reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at www.internol.net.

PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.