



## MOXIETECH LC 220-EP

### PRODUCT DESCRIPTION:

MOXIETECH LC 220-EP is an extreme-pressure grease fortified with a solid lubricant for enhanced performance. It exhibits exceptional resistance to water washout and provides superior protection against wear and corrosion for lubricated components. This grease is ideal for shock-loaded, heavy-duty bearings operating in wet conditions and is also well-suited for off-road applications and fifth-wheel lubrication.

### APPLICATIONS

MOXIETECH LC 220-EP is recommended for the lubrication of shock-loaded, heavy duty bearings working in wet conditions. It is also suitable for off-road applications and fifth-wheel lubrication.

### PRODUCT ADVANTAGES

- The operating temperature range is from -25°C to 130°C
- Effective extreme pressure properties
- Enhanced load-carrying and wear protection properties
- Good pumpability
- Good water washout properties

### TYPICAL PROPERTIES:

PARAMETERS	TEST METHODS	TYPICAL VALUE
NLGI Grade	-	2
Thickener Type	-	Lithium - Calcium
Base Oil Type	-	Mineral
Appearance	Visual	Smooth & Homogenous
Color	Visual	black
Work Penetration @25°C	ASTM D217	265-295
Copper Strip Corrosion 24hrs @100°C	ASTM D4048	1b
Dropping Point, °C, Min	ASTM D2265	180
Four Ball Weld Load, Kgf, Min	IP 239	315
Operating Temperature Range °C	INTERNAL	-25 to 130
Base Oil Viscosity @40°C (Cst)	ASTM D-445	220

**DISCLAIMER:** The test data presented above is indicative and not a strict specification, as it may vary within acceptable production tolerances. Internol reserves the right to update or modify this test data. For the most accurate and current information, please refer to the latest version of this Technical Data Sheet (TDS).

### HEALTH & SAFETY, ENVIRONMENT:

Continuous or repeated exposure to oil may lead to skin problems. Avoid contact with the oil. In case of contact, wash thoroughly with soap and water. Do not dispose of used oil in drains or the environment. Dispose of it at an authorized used oil collection point. For additional safety information, please refer to the MSDS available on our website at [www.internol.net](http://www.internol.net).

### PROTECT THE ENVIRONMENT:

Take used oil to an authorized collection point. Comply with local regulation. Do not discharge into drains, soil or water.